

DSP4042/DSP4053/DSP4064

All weatherproof landscape speaker



Features

- Commercial PA system speaker, with 3 mounting methods: wall-mounted, floor-stand and pendant type
- IP66, all weatherproof speaker for indoor and outdoor use
- Rated output power 20W/30W/40W at 8Ω and 70V/100V with power tap
- 1×4", 1×5.25" and 1×6.5" for bass driver and 1×1" for treble driver
- Quick installation with water-proof brackets
- White and black color for option
- Ideal for garden, parks, hotels and other outdoor activities

Description

The speaker is a combination of design and great sound. With the high-class woofer, it brings outstanding sound quality to users. With high temperature resistance and IP66 weatherproof, it can be used in indoor as well as outdoor. With the special brackets, the speaker is easy to be mounted under various angles in corners or on solid surfaces such as walls or ceilings.

This speaker with built in 70V/100V and 8Ω power tap, you can select different power for different occasion, rated power is 20W/30W/40W available, each speaker with three different installation type: Wall-mounted with bracket, you can install on the wall; Floor-stand with stake, you can install in your backyard; Pendant type with safety rope, you can hang the speaker in your room.

This speaker with our own mould and it's ideal choice for garden, parks, hotels and other outdoor activities.

Specification

Model	DSP4042	DSP4053	DSP4064
Woofer	4" PP Cone	5.25" PP Cone	6.5" PP Cone
Tweeter	0.75" Silk Dome	1" Silk Dome	1" Silk Dome
RMS Power	20W	30W	40W
Frequency Response (±3dB)	120Hz-20kHz	110Hz-20kHz	100Hz-20kHz
Nominal Impedance	8	8	8
Sensitivity	83	84	85
Transformer	8Ω-0-20W-10W-5W-2.5W	8Ω-0-30W-15W-7.5W-3.75W	8Ω-0-40W-20W-10W-5W
IP Level	IP 66	IP 66	IP 66
Product Dimension (mm)	138×190 (5.4"×7.5")	170×240 (6.7"×9.4")	208×280 (8.2"×11")