


Microphone Cable Stage 22 Highflex; 2 x 0,22 mm²; PVC Ø 6,40 mm; black

Art. No.: 200-0001

ANALOG

OFC



General Data

Article number :	200-0001
Name :	Stage 22 Highflex
EAN :	4049371001830
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Installation
Application :	Microphone Cable
Colour :	black
BPVo-Euroclass :	Fca

Technical Data

Signal transmission :	symmetrical
Construction :	(2LI2Y0,22mm ²)DY
Jacket material :	PVC
Jacket Ø [mm] :	6,40
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	0,22
Inner conductor Ø (audio) [mm] :	0,53
AWG (audio) :	24
Shielding :	Copper spiral shielding with 0.10 mm indiv. strands
Shielding factor [%] :	99
Copper strands (audio) :	28
Copper strand Ø (audio) [mm] :	0,10
Weight per 1 m [g] :	47
UV-resistant :	yes
Fire load per m [kWh] :	0,22
Style variant :	round
Packing :	100 m spool
Packing :	500 m spool
Temperature min. [°C] :	-20
Temperature max. [°C] :	70
Width [mm] :	6,4
Height [mm] :	6,4

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	68
Capac. cond./shield. per 1 m (audio) [pF] :	130
Impedance [Ω] :	100
Insulation resist. per 1 km [GΩ] :	1

Insulation resist. per 1 km (audio) [GΩ] :	1
Conductor resistance per 1 km [Ω] :	87
Shield. resistance per 1 km [Ω] :	30