



Top Class speaker, rectangular, frameless, 3-way built-in or plasterboard, **HI-FI**.

Ideal for Home Cinema systems or high quality audio systems.

Loudspeaker: woofer 20 cm Kevlar.

Midrange 8 cm Kevlar.

Dome tweeter 2,5 cm neodymium, silk and titanium, eyeball (in case of installations in not optimal environments it allows to give directivity to high frequencies, while not decreasing quality of listening).

Silk and aluminium diaphragm.

Power 120W RMS.

Musical power 240W.

Suggested amplification from 10 to 150 W RMS.

Impedance 4-8 Ω selectable.

Frequency response 40-22000 Hz.

Sensitivity 89 dB / 1W/1mt.

Dispersion angle 120° (V/O)

Speaker dimensions (WxHxD) 262x367x112 mm.

In-built hole (WxH) 325x222 mm.

Weight 3,1 Kg

Installation on plasterboard, wood walls or similar: no accessories needed, the speaker is provided in the

VIVALDI

rear with hook-shaped anchors for stable fixing.

Installation in-wall: by means of in-built case [Vivaldi Ulisse SR3PLUS](#).

White colour RAL9016. (view [Vivaldi Giove GIADA20HPF.R](#))

Cabinet: ABS with metal protection grille.

Working temperature from -20° to +65°.

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice



Images

Vivaldi Giove GIADA20HPF



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272