



# 5.1 PACK DÔME FLAX - 5 DÔME FLAX & SUB AIR

## Specification sheet

*Dôme is a high-end product, Made in France, focusing on miniaturization as much as on high-tech. With its sleek design and lacquered finish, Dôme suits each and every living spaces (on a table, mounted to a wall or an optional stand) and blends in perfectly with a flat screen. Thanks to its Flax cone, sandwich cone made of linen, this 5.1 system gets an important improvement in definition and intelligibility of dialogues as well as a larger spacialization thanks to a better linearity of the frequency response. The system is complemented by the intense and deep sound of Sub Air subwoofer. Wireless, Sub Air sets up without all cables constraints. Its flat innovative design and its high-gloss lacquered "Piano" finish perfectly fit into all kinds of spaces. This high-fidelity Home-Cinema pack will plunge you into the heart of the seventh art works.*

Patent N° WO 2014/106713 A1



### Key points Dôme Flax

- High-fidelity speaker, patented Flax technology
- Focal sound with advanced technologies
- Integrated speaker: in wall, in ceiling, on furniture or standing
- High-gloss lacquered Aluminium body
- Made in France

### Key points Sub Air subwoofer

- Install it wherever you want thanks to the wireless connection (wireless transmitter included)
- High-gloss lacquered "Piano" finish



|                             | Dôme Flax satellite                                                      |
|-----------------------------|--------------------------------------------------------------------------|
| Type                        | 2-way compact sealed speaker                                             |
| Drivers                     | 4" (10cm) Flax mid-bass<br>1" (25mm) Al/Mg inverted dome tweeter         |
| Frequency response (±3dB)   | 80Hz - 28kHz                                                             |
| Low frequency point (-6dB)  | 72Hz                                                                     |
| Sensitivity (2.83V/1m)      | 88dB                                                                     |
| Nominale impedance          | 8 Ohms                                                                   |
| Minimum impedance           | 4 Ohms                                                                   |
| Crossover frequency         | 2500Hz                                                                   |
| Recommended amplifier power | 25 - 100W                                                                |
| Dimensions (HxWxD)          | 6 <sup>3/4</sup> x5 <sup>11/16</sup> x5 <sup>5/8</sup> " (172x144x143mm) |
| Net weight                  | 1,9 kg                                                                   |

| Type                         | SUB AIR, Flat bass-reflex subwoofer, integrated 150W BASH® amp |
|------------------------------|----------------------------------------------------------------|
| Speaker driver (diameter)    | 8" (21cm)                                                      |
| Bass cutoff frequency (-6dB) | 35Hz                                                           |
| Frequency response (+/- 3dB) | 40Hz-200Hz                                                     |
| Crossover cutoff frequency   | variable 50 Hz - 200 Hz                                        |
| Input panel                  | Left Right / LFE                                               |
| Continuous power output      | 110 W                                                          |
| Peak power                   | 150 W                                                          |
| Phase adjustment             | 0 - 180° switch                                                |
| Power functions              | ON Auto (1 W) OFF (0,5 W)                                      |
| Dimensions (HxWxD)           | 16.1"x14.2"x6.3" (410mmx360mmx160mm)                           |
| Weight                       | 17 lbs (7,65 Kg)                                               |

| Type                                     | Wireless connection   |
|------------------------------------------|-----------------------|
| Range in Meter                           | 15 meters (in a room) |
| Sound Sampling                           | 16 bits               |
| Sampling Frequency                       | 44,1kHz               |
| Coding delay (latency)                   | 13ms                  |
| Radio transmission powers or sensitivity | 0dBm                  |
| Radio transmission frequency band        | 2,4Ghz ISM band       |