



Top Class speaker, rectangular, 2-way built-in, **HI-FI, FRAMELESS**.

Ideal for Home Cinema systems or high quality audio systems.

Loudspeaker: woofer 16,5 cm Kevlar.

Dome tweeter 2,5 cm neodymium, silk and titanium, **eyeball (in case of installations in not optimal environments it allows to give directivity to high frequencies, while not decreasing quality of listening).**

Power 80W RMS.

Musical power 160W.

Suggested amplification from 10 to 100 W RMS.

Impedance 4-8 Ω selectable.

Frequency response 45-22000 Hz.

Sensitivity 88 dB / 1W/1mt.

Dispersion angle 120° (V/O)

Speaker dimensions (WxHxD) 219x306x89 mm.

In-built hole (WxH) 190x275 mm.

Weight 2,1 Kg.

VIVALDI

Installation on plasterboard, wood walls or similar: no accessories needed, the speaker is provided in the rear with hook-shaped anchors for stable fixing.

Installation in-wall: by means of in-built case [Vivaldi Ulisse SR2](#).

Colour white RAL9016, paintable (view [Vivaldi Giove GIADA16HPF.R](#)).

Cabinet: ABS with metal protection grille.

Working temperature from -20° to +65°.

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice



Images

Vivaldi Giove GIADA16HPF



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272